

Data Sheet

Reference 50773
No.:

Coil Reel & Straightener

Brand: ARKU
Model: RM30 35
YoM, approx.: 2002 used
Reconditioned:
Controls: electronic controls SIEMENS SIMATIC S7-315-DP



Overall Specifications (coil lines)

sheet width max.: 246 mm
sheet thickness max.: 5 mm
coil weight max.: 2.5 to

Decoiler

design: twin reel
sheet width max.: 300 mm
sheet width (min): 50 mm
coil weight max.: 2.5 to
mandrel expansion range from: 370 mm
mandrel expansion range up to: 430 mm

Leveller Unit

number of leveller rolls: 21
diameter of leveller rolls: 30 mm

Strip-Feeder

speed max.: 75 m/min

Electrical specifications

mains voltage: 400 V
mains frequency: 50 Hz

Additional Information:

Belt width: 83.3mm to 246.0mm, Belt thickness: 5.0mm Feed lengths: 155.0mm to 1178.0mm
Reversible reel: - Load capacity up to 2500 daN per side - Spreading range 370 - 430 mm - Jaw length max. 370 mm (radian dimension) with clearance for crane hooks, with hardened guides for spreading. . - with screw-on segments 470 - 530 mm - coil outside diameter up to 1650 mm - strip width 50 - 300 mm
Coil diameter: outside 1650 mm inside from 370 - 430 mm with screw-on segments from 470 - 530 mm Strip width: from 50 - 300 mm Strip thickness: 1.0 mm
Tensile strength: max. 400 N/mm²

Seller:

ProdEq Trading GmbH
Emanuel Unger
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
Emanuel.Unger@prodeq.ch

Photos & Documents

Reference No.: 50773

