

## Data Sheet

Reference No.:46301

## Pressa transfer

Brand: PLATARG  
 Model: 2513  
 YoM, approx.: 1996 partially overhauled  
 Reconditioned: 2017  
 Controls:



### Costruzione

sistema di azionamento:  
 eccentrica/crank  
 tipo della costruzione: H-frame,  
 monoblock  
 numero di bielle / cilindri: 7  
 numero di azioni slitta: 13  
 direzione di lavoro: da sinistra a  
 destra

### Forze

forza totale: 130 to

### Slitta

corsa: 197 mm

### slitta

registrazione slitta: 19 mm  
 numero dei colpi min.: 30 /min  
 numero dei colpi mass.: 70 /min

### Montaggio Stampi

altezza chiusura (corsa/colpo giù,  
 registrazione in a: 203 mm

### Dati elettrici di collegamento

potenza assorbita (totale): 30 kW

### Misure / pesi

Requisiti spazio -sinistra/destra-: 4090 mm  
 Requisiti spazio - davanti/dietro-: 1727 mm  
 Altezza sopra il pavimento: 3900 mm  
 Peso totale approssimativo: 32000 kg

### Accessori (pressa)

strip feeder: sì  
 tipo di avanzamento:  
 avanzamento rulli  
 tagliasfrido: sì  
 automazione pressa: sì  
 sistema transfer pinza: sì  
 barriere di protezione / porta di  
 sicurezza: sì  
 noise protection cabin: sì  
 acc. to actual accident protection  
 regulation: sì

### Additional Information:

Can be tested in operation Max. Flywheel speed: 760 1/min. Capacity on one stage approx. 25T Clutch engagement max. 10/min Air pressure 5.5 bar (min) - 5.8 bar (max) Total deceleration time Braking <250 ms Zig-Zag Stroke length 2 stages 152.4 mm (6") 2 stages 177.8 mm (7") 8 steps 196.85 mm (7 3/4") Closing height (to die holder) 203 mm (8") Plunger distance 127 mm Max. Shell height approx. 78 mm Max. Plate diameter (single-row punching) 114 mm Max. Panel diameter (double-row punching) 108 mm Brankamp press force monitoring (carried out by a Brankamp PK5000 device with 8 channels) SIEMENS temperature monitoring (temperature monitoring of the bearing points is ensured with Siemens elements - (own construction) Frequency converter of the main motor (was completely overhauled in 2017) Additional pneumatic valve terminal (valve terminal available with Rexroth components for 14 pneumatic connections)

### Seller:

Post-Venta Carreras S.A.  
 Antonio Vega  
 Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787  
 La Pobla de Claramunt, Spain  
 +34 938 088 099  
 antonio@prodeq.es

## Photos & Documents

Reference No.: 46301

