

Data Sheet

Reference No.: 48186

Механический пресс для вырубки точных заготовок

Brand: FEINTOOL
 Model: GKP F 250
 YoM, approx.: 1978 used
 Reconditioned:
 Controls:



Slide

Общее номинальное усилие: 250 to
 Ход: 61 mm
 Частота ходов, макс.: 60 /min
 Частота ходов (мин.): 15 /min

Counter Ram

nominal force: 75 to

V-Ring

nominal force: 75 to

Tool Dimensions

lower table (left-right): 540 mm
 lower table (front-back): 540 mm
 upper table (left-right): 540 mm
 upper table (front-back): 540 mm

Strip-Feeder

sheet width max.: 250 mm
 sheet thickness max.: 10 mm
 sheet length min: 1500 mm

Additional Information:

Installation space of the tools
 Front passage between the columns:
 Movable: 560 mm
 Fixed: 560 mm
 Side passage between the columns:
 Movable: 270 mm
 Fixed: 270 mm
 Tool height:
 Movable: 160 - 305 mm
 Fixed: 175 - 320 mm
 Vertical adjustability of the upper clamping plate:
 Movable: 145 mm
 Fixed: 145 mm
 Fine blanking table:
 Max. hydraulic stroke both movable and fixed: 15 mm
 Max. counterholder stroke in head, movable and fixed:
 13 mm
 T-slots in the clamping plates for movable M16, fixed
 M16
 Movable and fixed table travel: 6 mm

Seller:

Post-Venta Carreras S.A.
 Eduard Peña
 Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
 La Pobla de Claramunt, Spain
 +34 938 088 099
 edu@prodeq.es

Photos & Documents

Reference No.: 48186

