

## Data Sheet

Reference No.: 49661

## Моечные установки непрерывного действия

Brand: LPW  
Model: POWERLINE 600T2  
YoM, approx.: 2015 used  
Reconditioned:  
Controls: электронный контроль



### Surface Treatment, usable Process Space / Zone

length: 6000 mm  
width: 625 mm

### Габариты / вес

Требуемая площадь (длина): 6000 mm  
Требуемая площадь (ширина): 2655 mm  
Общая высота: 2400 mm  
Общий вес (около): 5000 kg

### Данные электр. Подключения

Общая потребляемая мощность: 125 kW  
Напряжение питания: 400 V  
Частота тока в сети: 50 Hz

### Additional Information:

Cleaning process: Zone Zone length Treatment time at 0.6m/min (0.4-2m/min) Feed approx. 600mm Infeed zone approx. 300mm Cleaning zone approx. 1000mm approx. 100s Neutral zone/blow-off approx. 500mm Rinsing zone approx. 800mm approx. 80s Neutral zone approx. 500mm Blow-drying zone approx. 1500mm approx. 180s, about 130° Celsius Total length of the system approx. 6000mm The throughput time is adjustable and depends on the required treatment time Workpiece size (in the direction of travel): ☐ Largest approx. 360x630x300 mm (lwxh) ☐ Smallest approx. 50x15x5mm (lwxh) Translated with DeepL.com (free version)

### Seller:

ProdEq Trading GmbH  
Michael Weishaupt  
Reckholder 1, 9527 Niederhelfenschwil, Switzerland  
+41 71 948 70 60  
michael.weishaupt@prodeq.ch

## Photos & Documents

Reference No.: 49661

