

Data Sheet

Reference 46990
No.:

presa za fino rezanje - hidraulična

Brand: FEINTOOL
Model: HFA 3000
YoM, approx.: 1996 used
Reconditioned:
Controls: PLC programabilno upravljanje SIEMENS S5



Press Design

drive system: hydraulic

Slide

total force (nominal): 300 to
stroke: 180 mm

slide (hydr. Press)

approximation velocity max.: 150 mm/s
working velocity min.: 5 mm/s
working velocity max.: 50 mm/s

Counter Ram

nominal force: 75 to
stroke: 25 mm

V-Ring

nominal force: 150 to
stroke: 25 mm

Tool Dimensions

lower table (left-right): 640 mm
lower table (front-back): 910 mm
upper table (left-right): 630 mm
upper table (front-back): 630 mm
shut height max.: 410 mm

Overall Specifications (coil lines)

sheet width max.: 300 mm
sheet thickness max.: 8.5 mm
coil weight max.: 1.5 to
feedstock transport direction:
front-back

Decoiler

design: cradle
max. diameter of coil: 1500 mm

Leveller Unit

sheet width max.: 300 mm
sheet width (min): 50 mm
sheet thickness max.: 8.5 mm
sheet thickness min.: 1.5 mm
number of leveller rolls: 7
diameter of leveller rolls: 95 mm

Strip-Feeder

feeder type: roll feeder
sheet width max.: 250 mm
sheet thickness max.: 16 mm
feeding step min.: 1 mm
feeding step max.: 999 mm
sheet length min: 500 mm
nominal force: 30 kN
band lubrication system: yes
band support rolls: yes

Crop Shear

cutting force: 360 kN

Electrical specifications

total power consumption: 65 kW

Dimensions / weights

total weight approx.: 2800 kg

Attachments -Fineblanking Press-

decoiler: yes
leveller unit: yes
waste cutter: yes
slug separator: yes

Additional Information:

with coil line FEINTOOL FTW 390/3

Seller:

ProdEq Deutschland GmbH Standort Hück
Thomas Berger
Weberweg 2, 42499 Hückerwagen, Germ
+49 2192 935 382
thomas.berger@prodeq.de

Photos & Documents

Reference No.: 46990



Video Template:
| <https://www.youtube.com/embed/sOLviko-E0k> |