

Data Sheet

Reference No.: 48186

presa za fino rezanje - mehanička

Brand: FEINTOOL
 Model: GKP F 250
 YoM, approx.: 1978 used
 Reconditioned:
 Controls:



Slide

| | |
|------------------------|---------|
| total force (nominal): | 250 to |
| stroke: | 61 mm |
| stroke rate (max.): | 60 /min |
| stroke rate (min.): | 15 /min |

Counter Ram

| | |
|----------------|-------|
| nominal force: | 75 to |
|----------------|-------|

V-Ring

| | |
|----------------|-------|
| nominal force: | 75 to |
|----------------|-------|

Tool Dimensions

| | |
|---------------------------|--------|
| lower table (left-right): | 540 mm |
| lower table (front-back): | 540 mm |
| upper table (left-right): | 540 mm |
| upper table (front-back): | 540 mm |

Strip-Feeder

| | |
|-----------------------|---------|
| sheet width max.: | 250 mm |
| sheet thickness max.: | 10 mm |
| sheet length min: | 1500 mm |

Additional Information:

Installation space of the tools
 Front passage between the columns:
 Movable: 560 mm
 Fixed: 560 mm
 Side passage between the columns:
 Movable: 270 mm
 Fixed: 270 mm
 Tool height:
 Movable: 160 - 305 mm
 Fixed: 175 - 320 mm
 Vertical adjustability of the upper clamping plate:
 Movable: 145 mm
 Fixed: 145 mm
 Fine blanking table:
 Max. hydraulic stroke both movable and fixed: 15 mm
 Max. counterholder stroke in head, movable and fixed:
 13 mm
 T-slots in the clamping plates for movable M16, fixed
 M16
 Movable and fixed table travel: 6 mm

Seller:

Post-Venta Carreras S.A.
 Eduard Peña
 Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
 La Pobla de Claramunt, Spain
 +34 938 088 099
 edu@prodeq.es

Photos & Documents

Reference No.: 48186

