

Data Sheet

Reference No.: 46510

Ekscentrična stiskalnica (C okvirja)

Brand: PME ERFURT
 Model: PE 200-1400 CMA
 YoM, approx.: 2012 used
 Reconditioned:
 Controls: SPS krmiljenje SIEMENS S7 300



Press Design

drive system: eccentric / crank
 frame design: C-frame, single sided
 feedstock transport direction: left to right

Press forces

total force (nominal): 200 to

Press Table

table surface (left-right): 1400 mm
 table surface (front-back): 800 mm

Slide

table surface (left-right): 1000 mm
 table surface (front-back): 600 mm
 spigot hole diameter: 65 mm

slide (mechan. Press)

slide adjustment: 110 mm
 stroke adjustment: yes
 stroke min.: 21 mm
 stroke max.: 220 mm
 variable speed: yes
 stroke rate (min.): 15 /min
 stroke rate (max.): 80 /min
 main drive power: 15 kW

Tool Assembly Dimensions

shut height (stroke down, adjustment up), BDC: 520 mm
 throat (C-frame): 420 mm

Dimensions / weights

total height: 3800 mm
 total weight approx.: 16100 kg

Attachments (presses)

decoiler: yes
 leveller unit: yes
 strip feeder: yes
 feeder type: roll feeder
 light barrier: yes
 2-hand engagement: yes
 acc. to actual accident protection
 regulation: yes
 European CE standards: yes

Additional Information:

- Roll Feeder PME SERVO 300, max. strip width 300 mm, max. strip thickness 3.5 mm
- Coil Line with decoiler and straightener PME
- Control as PILZ press safety control PSS with 3-fold redundant structure and self-diagnosis as well as a status and error display
- Control variant - touchscreen TFT color - incl. electronic cam switch unit with heat exchanger control and heat exchanger fuse, pivoting main control panel with touchscreen for visualization,
- Tool data management, counting systems, data transmission via Profibus,
- 2-hand control panel separately on movable stand

Seller:

ProdEq Deutschland GmbH Standort Hückeswagen
 Thomas Berger
 Weberweg 2, 42499 Hückeswagen, Germany
 +49 2192 935 382
 thomas.berger@prodeq.de

Photos & Documents

Reference No.: 46510

